

# CHAGNON

☎ 800 565-1723

[🏠](#) > [CHAGNON](#) > [HOOK LIFT HOIST SYSTEMS](#) > > DLH - Long Series

---

## DLH - LONG SERIES

---

### DESCRIPTION

---

#### HOOK-LIFT SYSTEM ADVANTAGES

**Safe:** Lifting and installing the equipment controlled inside the truck, the bens (dumpster) are manipulated securely by the articulated hydraulic arm.

**Light:** A minimum of weight for a maximum capacity.

**Precise:** Thanks to the articulated hydraulic arm and better visibility the operator can take bens quickly from the center or on small inclines.

**Fast:** The distinct used of this system permits faster operation

#### KEY FEATURES AND ADVANTAGES

---

JIB ARM ENGINEERED FOR DURABILITY AND BUILT FROM 100,000 PSI STEEL COMPONENTS.

LONGEST JIB STROKE IN THE INDUSTRY ALLOWING YOU TO HAUL MORE CONTAINER LENGTHS.

MAXIMUM DUMP ANGLE FROM 48° TO 51°, DEPENDING ON THE MODEL.

LOW PRESSURE HYDRAULICS FOR SAFER OPERATION AND EASIER MAINTENANCE. HOSES PROTECTED BY TUFF SHIELD.

HOLD DOWN HOOKER MOUNTED DIRECTLY ON FRAME.

ALL BUSHINGS ARE GREASABLE AND EASILY ACCESSIBLE.

INTERIOR CONTROL BOX WITH ERGONOMIC LEVERS AND MULTIPLE OPTIONS.

IDEAL EQUIPMENT FOR HOOKING PLATFORMS, DUMP BOXES, SALTERS, ETC.

OUTSIDE CONTROL VALVES ARE A STANDARD FEATURE ON ALL EQUIPMENTS.

CAN BE INSTALLED BY ANY DURALIFT DISTRIBUTOR IN NORTH AMERICA OR BY YOUR OWN CREW.

## TECH SHEET

MODEL SPECIFICATIONS		DLH-5020	DLH - 5022	DLH - 6022	DLH - 6524
GENERAL	Lift / Dump Capacity	50,000 lb.	50,000 lb.	60,000 lb.	65,000 lb.
	Length (A)	216"	240"	240"	260"
	Dry weight	5,250 lb.	5,675 lb.	6,350 lb.	7,575 lb.
	Dump Angle (B)	50°	50°	50°	50°
	Max Operating Pressure	2,750 psi	2,750 psi	2,500 psi	2,750 psi
	Hook height (C)	61 3/4"	61 3/4"	61 3/4"	61 3/4"
	Roll-off Container length * (D)	14 to 20'	16 to 22'	16 to 22'	18 to 24'
Main Cylinders	Quantity	2	2	2	2
	Stroke	72"	80"	80"	88"
	Bore	6.5" / 3.5"	7" / 4"	8" / 4"	8" / 4"
Jib Cylinder	Stroke (E)	48"	52"	52"	56"
	Bore	5" / 2.5"	5" / 2.5"	6" / 3"	6" / 3"
Truck Specs	GVW	45,000 lb. and up	60,000 lb. and up	60,000 lb. and up	60,000 lb. and up
	CA (F)	154 to 170"	175 to 190"	175 to 190"	190 to 210"
	Clear frame rail	228"	240"	240"	264"
	Frame height (G)	45" max	45" max	45" max	45" max

## OPTIONS

- Crochet rétractable permettant de prendre des hauteurs de crochets variables
- Fonction hydraulique supplémentaire
- Basse ou haute pression
- Support de toile

## PHOTOS





DLH-5022